RockStand®

by Warwick®





RS 20930 B/10 RS 20931 B/10 RS 20932 B/10

Product Contents:

- 1 x base plate
- 1 x frame piece for holding the mounting brackets
- 1 x mounting bracket for neck
- 1 x mounting bracket for instrument's body
- 3 x locking nut M8
- 3 x screw M4 x 50 mm (2")
- 3 x plastic dowel

Tools required:

- Phillips screwdriver
- hammer
- hammer drill with 6 mm masonry bit
- level
- pencil
- 1. Take the base plate which is to be screwed to the wall.
- **2.** Align the base plate at the desired position so that the protruding pin is horizontal with the opposite hole. Using the level as an aid, mark the holes with the pencil.
- 3. Should you wish to mount the wall hanger on a brick wall, please use the supplied dowels, and a power drill with a 6 mm masonry bit. In case your wall is made of other material, such as drywall or wood, the supplied dowels cannot be used. Please use according mounting screws and material. Now drill the holes deep enough for the screws (approx. 50 mm / 2").
- **4.** Insert the dowels into the drill holes in the wall, a hammer can be used as an aid.
- **5.** Now screw the base plate tightly to the wall using the provided screws and an appropriate Phillips screwdriver.
- **6.** Now fasten the brackets for the instrument's body and neck using the provided M8 locking nuts, tighten them by hand. Please note, the brackets must be opposite of the perforated plate attached to the frame piece, not on the same side.
- 7. Now insert the frame piece with the perforated plate facing the base plate in the desired position on the base plate. Fasten it with the provided M8 locking nut.

Now you can hang the instrument.

Not recommended for instruments with nitro-cellulose finish.





















RockStand® by Warwick®



Warwick GmbH & Co. Music Equipment KG, Gewerbepark 46, 08258 Markneukirchen / Germany

info@rockgear.us I www.warwick.de I shop.warwick.de I www.facebook.de/warwickmusicdistribution