



WA44

---

# Wylde Audio Overdrive

---

Celebrate the 20th anniversary of the explosive collaboration between Dunlop and Zakk Wylde with the MXR® Wylde Audio Overdrive. Custom built for Zakk's loud, tough, and relentless riffs and leads, this muscular stomp box will transform your amp into a heavy, chunky crunch machine.

[jimdunlop.com/wa44](http://jimdunlop.com/wa44)

---

## External Controls



- 1 FOOTSWITCH toggles effect on/bypass (red LED indicates on)
- 2 OUTPUT knob adjusts overall effect volume
- 3 TONE knob adjusts overdrive EQ
- 4 GAIN knob adjusts overdrive intensity

---

# Basic Operation

---

## Power

The MXR® Wylde Audio Overdrive is powered by a single 9-volt battery (remove bottom plate to install), a 9-volt AC adapter such as the Dunlop ECB003, or an MXR® Brick™ Series power supply.

---

## Directions

- 1.** Run a cable from your guitar to the WA44's INPUT jack and run another cable from the WA44's OUTPUT jack to your amplifier.
- 2.** Start with all knobs at 12 o'clock. Turn the effect on by depressing the footswitch.
- 3.** Rotate OUTPUT knob clockwise to increase effect volume or counterclockwise to decrease it.
- 4.** Rotate TONE knob clockwise for a brighter tone or counterclockwise for a warmer tone.
- 5.** Rotate GAIN knob clockwise to increase overdrive intensity or counterclockwise to decrease it.

---

# Specifications

Input Impedance	1 MΩ
Output Impedance	7.5 kΩ
Nominal Input	-22 dBV
Noise Floor*	-88 dBV
Bypass	Hardwire
Current Draw	2.2 mA
Voltage Requirements	9 volts DC

\* A-weighted